# DiECi



**APOLLO** 

26.6



di∈ci.com

## **PERFORMANCE**

Apollo 26.6 Vehicle model 2600 kg (5732 lb) Maximum capacity 5.73 m (18.8 ft) Maximum lifting height Maximum horizontal extension 3.2 m (10.5 ft)

Fork swiveling angle 129°

5510 daN (12387 lbf) Pull-out force Towing force 4400 daN (9892 lbf) Unladen weight 5100 kg (11244 lb)

Maximum climb angle 40 %

Max speed (referred to wheels with maximum permitted diameter)

30 km/h (18.6 mph)

2.87 s

Vehicle model Apollo 26.6 Getting off the basket 5.24 s Lifting 10.07 s 7.87 s Extension Retraction 4.37 s Forward swiveling 4.54 s

Reverse swiveling

Vehicle model Apollo 26.6 Brand YANMAR Nominal power 53.7 kW (72 HP) @rpm 2500 rpm Operation 4-stroke

Injection Electronic, Common Rail

Number and arrangement of cylinders 4, Vertical in line 3319 cm<sup>3</sup> (203 in<sup>3</sup>) Displacement

235 g/kWh (386.58 lb/Hp h) Consumption

2500 rpm @rpm Emission standards Stage V/Tier 4f

Catalyst + Particulate filter (DOC+DPF) Exhaust gas treatment

Cooling system Liquid

Intake Turbo compressor

Air filter Air pre-heating and air pre-filtering with dust separator

Vehicle model Apollo 26.6

Transmission type Single speed Hydrostatic transmission with variable displacement pump

Hydraulic motor Hydrostatic with continuous automatic adjustment

Reversal Electro-Hydraulic

With hydraulic pedal for controlled forward movement Inching

## **DIFFERENTIAL AXLES**

Vehicle model Apollo 26.6

Type of axles 2 steering, with 4 epicycloidal reduction gears

Type of steering 4 wheels / transversal / 2 wheels

Front axle Rigid Rear axle Swinging

Service braking Oil bath on front axle

Parking braking Negative actuation with electrical control

## **HYDRAULIC SYSTEM**

Vehicle model Apollo 26.6

Hydraulic pump type Gear pump for power steering and movements

Hydraulic pump capacity 80 l/min (21.1 gal/min) Max. operating pressure 23 MPa (3336 psi) Distributor control Proportional 4in1 Joystick Distributor type Single-lever hydraulic proportional

### **FILLING**

Vehicle model Apollo 26.6 Hydraulic system (total) 85 l (22.45 gal) Diesel tank 80 l (21.13 gal)

Vehicle model Apollo 26.6 Standard tires 12.0/75-18

DIMENSIONS			
Vehicle model	Apollo 26.6		
A	280 mm (11.0 in)		
В	985 mm (38.8 in)		
C	2350 mm (92.5 in)		
D	765 mm (30.1 in)		
F	3585 mm (141.1 in)		
G	4100 mm (161.4 in)		
Н	1980 mm (78.0 in)		
1	860 mm (33.9 in)		
L	1500 mm (59.1 in)		
M	1860 mm (73.2 in)		
P	1330 mm (52.4 in)		
Q	3400 mm (133.9 in)		
S	1485 mm (58.5 in)		
T	110 mm (4.3 in)		







